



















# Sliding Door Specifications

- Glazing in windows complies with AS 1288. Human Impact Requirements
- Purchaser to specify if door conditions vary from this
- These products are designed to 1000pa wind pressure and 150pa water pressure
- All frames are viewed from the outside

## Sliding Courtyard Doors

## Sliding Terrace Doors

STUD OPENING		1830	2420	2960	1830	2420	2960
FRAME		1810	2400	2940	1810	2400	2940
2127 2417	2107 2397						
		CD2118	CD2124	CD2129	TD2118	TD2124	TD2129
		2725	3620	4480	2725	3620	4480
		2705	3600	4460	2705	3600	4460
2127 2417	2107 2397						
		CD2127	CD2136	CD2145	TD2127	TD2136	TD2145
		3566	4746	5826	3566	4746	5826
		3546	4726	5806	3546	4726	5806
2127 2417	2107 2397						
		CD2135	CD2147	CD2158	TD2135	TD2147	TD2158

These configurations / sizes are provided as a guide. Canterbury can manufacture this product to suit most openings. Timber and aluminium flywire screens are available with this product. Lockable and non-lockable hardware is also available. Options are only available at time of ordering Please note: Some frames may require doors or sashes removed upon delivery and or onsite glazing depending on size



1 Standard 2 Colonial Bar 3 Colonial Bar

1 Standard 2 Colonial Bar 3 Colonial Bar 4 Federation Bar 5 Heritage Bar

Our commitment to continual product development necessitates that sizes and specifications may change without notice.